

FORMLINE Form Metrology



Flexible and efficient form measurement

We deliver solutions that help you optimize your manufacturing process regarding qualitative and economic objectives.

We, the Industrial Metrology Division of the Jenoptik Group, are one of the leading international specialists in high-precision, tactile and non-tactile production metrology.

Our services range from complete solutions for different measuring tasks such as the inspection of surface and form as well as determining dimensions, throughout every phase of the production process including final inspection or in the metrology lab.

Our decades of experience in tactile, optical and pneumatic measurement combined with our global sales and service support network brings us close to you, our customers, enabling us to provide optimal support as a reliable partner.

Our team is looking forward to your inquiry!

Jenoptik – Sharing Excellence









Measuring solutions for your applications

Measuring systems of our FORMLINE series offer you extensive evaluation possibilities for shaft type and cubic workpieces (depending on the system):

Form tolerances

- Straightness
- Roundness
- Flatness

AR

AB

Y

К

Ø 3x

В

Rz No twist

Е

• Cylindricity

Position tolerances

- Parallelism
- Perpendicularity
- Angularity
- Coaxiality, concentricity

Run-out tolerances

- Radial run-out
- Axial run-out
- Total radial run-out
- Total axial run-out

Specific parameters

- Diameter
- Conicity
- Position deviation
- Length
- Stroke radius
- Crowning





Get better measurements

... with versatility

The modular design of our FORMLINE solutions guarantees maximum flexibility for a wide range of applications. Our product line includes compact roundness measuring devices, standard and custom CNC measuring systems for the determination of all form and positional tolerances as well as combined form and surface roughness measuring systems. You also get solutions for large, heavy and cubic workpieces or specific crank shaft and cam shaft measurements or form measurement in cylinder bores.

... with professional metrology

FORMLINE solutions are the result of our decades of experience and extensive know-how in form metrology. They boast explicit measurements according to standards, easy operation and professional evaluation of the measured values.

... in day-to-day operations

FORMLINE solutions measure with high accuracy in the measuring lab or in the shop floor. With a user-friendly evaluation software, they are easy to use and can be easily adapted to numerous measuring tasks thanks to an extensive range of accessories.

... with speed

Time is money. That's why we focus on automated measuring runs and FORMLINE solutions, that offer optimized processes, adapted to the measuring tasks.

... with customized solutions

For your specific requirements, we develop measuring systems, that are adapted to your needs. You can rely on our experience in the development of customized solutions, for example for break disks, pistons, valves, conrods or injection parts.



Form measuring systems







Measuring systems for cylinder bores

Model	Brief description	Page
F50, F135, F155	Compact and ergonomic form measuring systems	6 – 7
F435, F455	Fully automatic measurement of all form and positional tolerances, roughness and twist measurement as an option	8 – 9
roundscan	Combined form and roughness measuring systems with optional twist measurement	10 – 11
FMS8200	Spindle measuring machines for heavy workpieces with a large measuring volume	12 – 13
TURBO FORM	Evaluation software for F series, roundscan and FMS	14 – 18
CFM, CCM	Measuring machines for crank shafts and cam shafts	26 – 27
TURBO SHAFT	Evaluation software for CFM and CCM	28 – 29
incometer	Measuring systems for form and roundness in cylinder bores	32 – 35
INCOWIN	Evaluation software for incometer	36 - 39



Accurate and cost-efficient roundness measurements

With the compact F50 form measuring system you perform roundness measurements quickly and accurately.

Highlights HOMMEL-ETAMIC F50

- Universal roundness measuring system with extensive evaluation possibilities
- Professional print reports for documentation of your production quality
- Secure and simple operation via the Windows-based evaluation software
- Fast and efficient measurements
- High-quality, maintenance-free air bearing for maximum precision at all times
- Compact and robust desktop device, which is ideal for flexible use during production

- Highly accurate air bearing rotary table with a diameter of 150 mm
- Menu-guided manual centering and leveling
- Measuring probe with adjustable measurement force and large measuring range
- Continuously adjustable measurement speed
- Manual Z and R axes
- Simplified software user interface with all the key functions in one view
- Optional tilt arm FS1 for variable probing positions

Model	Workpiece weight	Distance C/Z axis	ø measurable	Measuring height	Centering/ leveling	Measuring axes	Option roughness
F50	25 kg	195 mm	300 mm	320 (560 ¹) mm	manual	С	no





Form measurement of precision parts made easy

The F135/F155 measurement systems are the best choice for measuring roundness and cylindricity of precision parts.

Highlights HOMMEL-ETAMIC F135/F155

- Universal system for cylinder form measurements with extensive evaluation functions
- Automated measurement runs
- Professional print reports for documentation of your production quality
- Two models to choose from, depending on the workpiece length
- Extensive range of probes for numerous measuring applications
- Capable assistant for easy creation of test plans
- Optional measuring R axis for flatness measurements

- Highly accurate air bearing rotary table with a diameter of 150 mm
- Menu-guided manual centering and leveling
- Measuring Z axis for cylinder form and straightness measurements
- Probe protected against collisions
- New generation of probes with magnetic coupling for fast probe arm changes
- Tilt arm FS1 for variable probing positions, even on complex workpieces

Model	Workpiece weight	Distance C/Z axis	ø measurable	Measuring height	Centering/ leveling	Measuring axes	Option roughness
F135	25 kg	275 mm	340 mm	350 mm	manual	С, Z	no
F155	25 kg	275 mm	340 mm	550 mm	manual	С, Z	no



hommel etamic F435

Fully automatic measuring of all form and positional tolerances

The F435 and F455 form measurement systems allow you to determine all form and positional tolerances in a precise and reliable manner.

Highlights HOMMEL-ETAMIC F435/F455

- Precise measurement of roundness, cylinder form and flatness
- High degree of automation thanks to automatic centering and leveling of the workpiece and CNC controlled measuring axes
- Easy CNC programming and workpiece-specific measurement documentation
- Capable evaluation software for determination of all form and positional tolerances
- For demanding measuring tasks in series production or for frequently changing tasks in the metrology lab
- Optional roughness and waviness measurement with free probing system in Z-direction
- Optional twist measurement according to MBN 31007-07

- Highly accurate air bearing rotary table
 (250 mm) with automatic centering and leveling of the workpiece
- Three motorized measuring axes
- Vertical measuring axis with a measurement range of either 350 mm or 550 mm
- New generation of probes with magnetic coupling for fast probe arm changes
- Tilt arm FS1 for perfect probe positioning, even on complex workpieces
- Available as a desktop device or as an ergonomic measuring station
- Optional instrument table with air damping or spring elements





Measurement of roughness and form with double-tipped probing system and magnetic coupling



Motorized tilt and rotation module MDS

hommel etamic F455

Optional roughness and waviness measurement

Thanks to the new FT1.1 probe generation and a double-tipped probing system, roughness and waviness measurements can be performed in addition to form measurements. And all this in a single clamping operation, saving you both time and money.

Fully automatic measurements

Thanks to the optional motorized tilt and rotation module MDS, the probe is always positioned in the optimum probing position on the workpiece, thus allowing for the measuring of complex workpiece geometries without interrupting the CNC run.

• One motorized axis for tilting (90°) and one for rotating (270°) the probe for reaching measurement positions that are hard to access

Compact desktop device

Depending on requirements, the F435 and F455 measurement systems are available either as a compact desktop device or integrated into an ergonomic measuring station.



HOMMEL-ETAMIC F435, desktop device

Model	Workpiece weight	Distance C/Z axis	ø measurable	Measuring height	Centering/ leveling	Measuring axes	Option roughness
F435/F455 desktop	40 kg	325 mm	430 mm	350/550 mm	automatic	C, Z, R	no
F435/F455 station form	40 kg	325 mm	430 mm	350/550 mm	automatic	C, Z, R	no
F435/F455 station roughness	40 kg	325 mm	430 mm	350/550 mm	automatic	C, Z, R	yes, Z axis



Depending on the measurement task, the combined form and roughness measurement systems from the roundscan series can be configured to create the measurement situation that best suits your requirements.

Highlights HOMMEL-ETAMIC roundscan

roundscan

homme

- Saving of time: very fast, fully automatic centering and leveling and CNC controlled measuring axes for save measuring, even on complex workpieces
- · Flexibility: combined form, roughness and twist measurements in a single clamping operation with no probe arm changes; small parts such as valves can be measured with a small measuring circle
- Ergonomics: optimized design for convenient standing or sitting operation of the measuring system

- Highly accurate air bearing rotary table with impressive rigidity for consistently high precision
- Vertical measuring axis available in three different heights, depending on requirements
- Basic version for form measurement with 1 µm resolution of the R/Z axis and 20,000 points in the C axis
- High Resolution version (HR) for combined form and roughness measurements with 0.1 µm resolution in the R/Z axis and 720,000 points in the C axis, as well as integrated linear scale and air damping with active level control







MDS4 with double-tipped probing system FT3 with collision protection



Height-adjustable evaluation unit

Fully automatic measurements with innovative probe system for efficient measurement of form, roughness and twist

- CNC controlled tilt and rotation module MDS4 for measurements at any position on the workpiece
- Double-tipped probing system for measurements with two different probe tips for form and roughness
- Adjustable and switchable probe force for measurements in accordance with standards
- Probing system can be switched from form to roughness during the CNC run
- High resolution of the axes for a minimal measuring point distance for roughness measurements
- Low measurement speed from 0.2 mm/s can be run
- Only very low basic interference of the measuring axes, even at maximum resolution
- Form and roughness measurements can be programmed fully automatically; no retooling times for fast and reproducible measurements
- Magnetic probe arm coupling for fast changing of the probe arm and protection in case of collisions

Ergonomic measuring station

- Height-adjustable, tiltable evaluation unit
- Convenient standing and sitting workstation
- Lockable cabinets for safe storage of evaluation computer and printer
- Control panel for performing key operations while maintaining a view of the workpiece and probe
- Integrated probe arm rest

Model	Workpiece weight	Distance C/Z axis	ø measurable	Measuring height	Centering/ leveling	Measuring axes	Option roughness (HR models)
roundscan 535	60 kg	370 (420*) mm	430 (530*) mm	350 mm	automatic	C, Z, R, X, Y	yes, C, Z, R axes
roundscan 555	60 kg	370 (420*) mm	430 (530*) mm	550 mm	automatic	C, Z, R, X, Y	yes, C, Z, R axes
roundscan 590	60 kg	370 (420*) mm	430 (530*) mm	900 mm	automatic	C, Z, R, X, Y	yes, C, Z, R axes



* on request

hommel etamic FM58200

Spindle measuring machines for large and heavy workpieces

The specific machine design of the FMS8200 spindle measuring machine with a rotating probing system and five measuring axes offers you a flexible solution for the automated measurement of all form and positional tolerances on large and heavy workpieces.

Highlights HOMMEL-ETAMIC FMS8200

- Fully automated measuring runs with extensive evaluation possibilities
- Freely movable operator terminal for the entire machine control
- Comprehensive collision protection for a long service life and increased productivity
- Automatic changeover of the probing direction for different measurements in a single clamping operation
- Easy changing of the workpiece thanks to large measuring and travel ranges of the axes

- Rotating probing system with automatic weight balance
- Automatically movable air bearing X-Y table with large support area
- In X-Y table integrated axes (A, B) for automatic workpiece alignment
- X, Y and Z axes with straightness measuring function
- Five measuring axes, two alignment axes as well as optional movement axis for the measurement of V motor blocks
- Automatic setting of the probing system to the workpiece diameter
- Especially suited for cylinder heads, motor blocks, large liners, gear boxes, crank shafts, large-bore pistons, etc.





hommel etamic FM58200

Crank shaft measurement

The crank shaft measurement arm is used for axial and radial measurements on main bearings and pin bearings with no probe changes. The measurement arm is available with either an automatically or manually rotating probe.

Crank shaft measurement with specific probe arm



Manual or automatic tilt module

The tilt module enables manual or automatic positioning of cylinder heads or motor blocks (depending on version). Valve seats and cylinder bores of V motor blocks can be completely CNC measured.

Manual tilt module

Model	Workpiece weight	X axis	Y axis	Measuring height	Workpiece alignment	Measuring axes	
FMS8200	300 kg	800 mm	300 mm	1300 mm	automatic	C, Z, R, X, Y	

hommel etamic *тикво FORM*

Software with clear user guidance for reliable measurement evaluation



Creating test plans

By clicking the mouse you select the required characteristic. The wizard guides you simply and safely through all the necessary steps.



Automatic alignment

Alignment is semi-automatic or fully automatic (depending on the device version) and is supported by the software to optimum effect.

The graphical, function-oriented TURBO FORM user interface ensures simple operation, even when performing complex measurement tasks:

- User-friendly interface with clear icons
- Simple definition of measurement positions and axis references
- Direct transfer of positions via teach-in
- Simple CNC programming using pictograms
- Fully automatic alignment and measurement of workpieces
- Comprehensive profile analysis and complete documentation of the measurement results

Highlights HOMMEL-ETAMIC TURBO FORM

- For all F series, roundscan an FMS8200 systems
- Clear program flow
- Evaluation in accordance with standards
- Convenient test plan management
- User-defined presentation of measuring reports
- Numerous options for special applications
- Fast evaluation algorithms for prompt results
- CNC modules, Fourier analysis and 3D analyses included in the standard scope of delivery
- Automatic saving of PDF reports





Measuring

Depending on the device type, measuring is performed manually or fully automatically via a CNC measuring program. The measuring profile can be viewed, allowing an evaluation to be performed while the measuring process is still underway.

Analysis and documentation

After scanning the workpiece, the measuring profiles are displayed clearly and in accordance with standards in (3D) diagrams. Measurement data can also be exported via an optional interface.

Automatic measurement runs: CNC

A CNC run is quicker than a manual measurement sequence and provides user-independent, reproducible results. The aligned workpiece is (automatically) measured at the measuring positions defined in the test plan. Printing and saving of the reports can be integrated directly into the automatic run.

CNC programs are created by single steps in the teachin mode and can then be changed step by step, either as a total measurement run or in single steps.

Fourier analysis

The measured profile is deconstructed into its spectral components and displayed as a graphic. Tolerance limits are defined with a limiting curve and a warning limit in order to detect recurring, high-frequency profile parts, such as chattermarks.

Software options for the evaluation of special measuring tasks



Line form



Cone



Linear form piston

Line form

Evaluation of the line form by a nominal curve with even tolerance band.

Angular sector

Determination of the greatest roundness error within a defined angle segment.

Fourier synthesis

Extraction of individual frequency ranges. Characteristics, which are then formed, no longer contain these waves.

Cone

Calculation of the cone angle from two polar or two linear profiles. Determination and clear 3D display of conical form and run.

qs-STAT[®] interface

Certified according to AQDEF. Transfer of the measuring data to the statistics package qs-STAT® for process data analysis.

ASCII export interface

Export of calculated characteristics and their measured values in ASCII format for further processing in other software programs such as Excel.

Piston measurement

Evaluation of non-standardized characteristic types on pistons, e.g. evaluation of the ovality, reference bolt axis or linear form.

Brake disk measurement

Evaluation of certain important properties of brake disks such as wobble, thickness difference, waviness and wear measurement.

Evaluation of roughness, waviness and profile



Roughness parameters and roughness profile



Measurement report

This optional module for the F435 and F455 models, as well as the High Resolution (HR) versions of the roundscan, enable fast, simple calculation, evaluation and graphical representation of all standard roughness, profile and waviness parameters in accordance with DIN/EN/ISO/JIS standards.

Highlights roughness option for HOMMEL-ETAMIC TURBO FORM

- Various standard forms for evaluation
- Simple, clear configuration of measurement conditions
- Individual combination of parameters depending on the measurement task
- A wide range of display options simplifies profile analysis, e.g. superposition of several profiles, zoom, filter or fault extraction
- Free and individual design of screen and print forms
- Clear display of all form and roughness parameters in a characteristics table
- The key information is visible at a glance via the tolerance output and the status display

Automatic roughness evaluation (CNC)

Roughness measurement positions are integrated into the CNC run by the appropriate program button. Measurement conditions such as probing force are adapted automatically. The results are displayed directly in the automatic measurement run and printed as required. They can also be saved as a PDF file or exported via the ASCII or qs-STAT[®] interface (optional).

Twist measurement according to MBN 31007-7

Twist refers to periodic structures which are comparable with the course of a thread. Magnified many times, it is visible as a micro-grinding structure. Twist structures at the sealing surfaces of shafts occur during grinding and impair the sealing function between the shaft and the sealing ring.

The most important properties of these structures can be determined with a 3D evaluation of the surface. The contact zone of the shaft is measured as a 3D area with a roughness stylus tip over a series of envelope line profiles. This allows a graphic representation of the twist structure as well as calculation of the twist parameters.



Twist measurement with a roughness stylus tip

Twist parameters

The F435, F455 and roundscan systems support the current version of the MBN 31007-7 Daimler standard from 2009. This means that all parameters such as Number of threads DG, Twist depth Dt [μ m], Period length DP [mm], Feed cross section DF [μ m²], Feed cross section per revolution DFu [μ m²/r], Contact length in percent DLu [%] and Twist angle D γ [°] can be determined. Due to the optimized evaluation algorithms, the measurement results are much more stable. The reduction of the standard evaluation length from 5 mm to 2 mm reduces time considerably.

TwistLive® analysis method

With this modern analysis method for all roundscan systems, the normal measurement time may be reduced by 75 %. During the measuring progress, a results forecast of the twist parameters is already possible – live!





Display of twist structure in detailed scaling



Display of original profile (green) and twist profile (blue)

Chucks, instrument tables and tilt modules for F series and roundscan

We offer a wide range of standard and custom accessories for handling even the most complex workpieces.

Chucks

With three, six or eight hardened clamping jaws for secure clamping of the workpieces on the rotary table.

Chuck FX70

Chuck range Internal 18–62 mm External 2–68 mm Art. 232 036



Chuck FX100

Chuck range Internal 28–95 mm External 2–95 mm Art. 232 357

Chuck FX150

For 250 mm rotary table Chuck range Internal 46–140 mm External 2–140 mm Art. 232 359



Chuck FX150

For 150 mm rotary table Chuck range Internal 46–140 mm External 2–140 mm Art. 507 001



Motorized tilt and rotation module for F435 and F455

With this module the probe is always positioned in the optimum probing position on the workpiece. Thus complex workpiece geometries can also be measured fully automatically.

Art. 1006 0796



Instrument tables

For F series desktop devices	
GTS with drawers	Art. 232 900
GTS-K	Art. 232 901

For F435 and F455

GTF-3 with			
spring elements	Art.	1006	3184
GTF-3 with			
air damping	Art.	1006	3185

Probe arms – basis for high-precision measurement

Probe arm set FTS1 for F50

To cover the most common measurement tasks. Art. 230 580



The components of the probe arm set may also be ordered separately:

0.0							
Art. IM05 1210							
Probe tip M2 KU0500/-R L20 D0.7/14.0							
Art. IM05 1209							
Art. 519 520							
Probe tip FO KU1500/-R L20 D2/18.5							
Art. 243 877							
Art. 241 712							
Probe tip FO TO250-8000/60H L40 D2/40							
Art. 243 681							
Art. IM05 1215							





Probe arm FT-R-L100-KU1.5-H-5x6

L = 100	mm; 5	mm	probe	ball	Art.	230	615
---------	-------	----	-------	------	------	-----	-----

Probe arms FT-HR-L040-D2 and FT-HR-L100-D2

mm bore for inserting probe tips.	
= 40 mm	Art. 230 630
= 100 mm	Art. 230 634

Probe arm FT-HA-L020-M2

M2 thread for screwing on probe tips. L = 20 mm Art. 230 561

Ceramic probe arms for F50

Available in standard and custom sizes, which can be quickly and easily adapted to a variety of measurement situations. Below are examples of different types of probe arms.







Probe arms FT-HR-L040-M2 and FT-HR-L100-M2

2 mm thread for screwing	on probe tips.
L = 40 mm	Art. 244 940
L = 100 mm	Art. 244 941
Probe tip M2 KU1500/-R L	.10 D1.5/4.0
With 1.5 mm ruby ball	Art. IM06 3935

Probe arms FT-HR-L040-D2 and FT-HR-L100-D2

For inserting 2 mm probe tips. For measurements on ground and slightly soiled measurement positions. L = 40 mm Art. 256 720

L = 100 mm	Art.	1000	1880
Probe tip FO KE300/90H L	16 D2	/16	
2 conical tips	Art.	243 9	38

Probe arm FT-R-L097.75-KU0.15-H-1.5x72.7 With tip contacting at an angle. For measurements on envelope lines. Art. 241 561





Special version for measurements on end surfaces, in bores above 3 mm and on the

Probe arm FT-AR-L040/072.25-S

Art. 256 729



Probe arm FT-A-L040-KE5-90GD-FL

For twist measurement.	L = 40 mm.	
Diamond tip 90°/5 µm	Art. 513	140

Probe arms for individual measuring tasks

Probe arm set FTS3 for F135/F155, F435/F455 and roundscan 535/555/590

To cover the most frequent measurement tasks. Art. 1002 9224



The components of the probe arm set may also be ordered separately:

Probe tip FO KE300/90H L10 D2/10

L = 10 mm; 2 cone tips	Art. 519 520
Probe tip FO KE300/90H L35 D2/35	
L = 35 mm; 2 cone tips	Art. 241 712
Probe tip FO KE300/90H L10.4 D4-2	/5.4-5
L = 10.4 mm; cone tips	Art. 243 519
Pin wrench M2	Art. IM05 1215
Probe tip extension M2V L60 KE D3.	0/60.0
L = 60 mm; M2 thread	Art. 1003 4259
Probe tip M2 KU1000/-R L20 D1.0/1	4.0
L = 20 mm; 1 mm ruby ball;	
M2 thread	Art. IM05 1207



Probe arm FTM-HR-L038*098-D2*D2

Two 2 mm bores for inserting probe tips. The probe tip at 38 mm is suitable for the outside measurement; the probe tip at 98 mm is used for measurements in bores. L = 38 mm + 98 mm Art. 1003 0456



Probe arm FTM-HA-L018-M2

M2 thread for screwing on probe tips.				
L = 18 mm	Art.	1000 3942		
Probe tip extension M2V L60 KE D3.	0/60	0		
L = 60 mm; M2 thread	Art.	1003 4259		
Probe tip M2 KU1000/-R L20 D1.0/14.0				
L = 20 mm; 1 mm ruby ball; M2 three	ad			
	A	IN 40E 1007		

Art. IM05 1207

Probe arms for form measuring systems with measuring axes

Standard probe arm and probe tip

To cover the most frequent measurement tasks. Included in the scope of delivery of the form measuring systems F135/F155, F435/F455 and roundscan 535/555/590.



Probe arm FTM-R-L038-KU1.0-R

L = 38 mm; 2 mm ruby ball

Art. 1006 5094

Special probe arms for measurements in small bores from 3 mm



Probe arm FTM-R-L099-KE0.3-60H

For form measurement. L = 99 mm. Cone tip $60^{\circ}/0.3$ mm Art. 1001 1703



Probe arm FTM-R-L098-KE5/60-D

For roughness measurement. L = 98 mm. Diamond tip 60°/5 μ m; 45° mounting Art. 1004 0375 Diamond tip 60°/5 μ m; 90° mounting Art. 1004 0389



Probe arm FTM-HR-L038*108-KE0.5-90H-KU0.5H

For measurements on end faces, in bores and on the
bottom surfaces of bores.Probe armArt. 1005 2509Probe tip FO KE500/90H L50 D2/50Cross pinArt. 1005 2561

Probe arms and probe tips with thread

For form measuring systems F135/F155, F435/F455 and roundscan 535/555/590.



Probe arms FTM-HR-Lxxx-M2

Lateral M2 thread for screwing on probe tips. L = 38 mm Art. 1000 3938 L = 98 mm Art. 1000 9711 L = 158 mm Art. 1000 9714 l = 200 mmArt. 1003 8257



Probe arm FTM-HR-L038*098-M2*M2

Two lateral M2 threads for screwing on probe tips. L = 98 mm + 38 mm Art. 1002 4596

Probe tips M2 with ruby ball

Standard probe tips for precise form measurement.

Probe tip M2 KU1000/-R L10 D1.0/4.0

L = 10 mm; 1 mm ruby ball Art. IM05 1208

L = 15 mm; 1 mm ruby ball Art. 1002 9794

Probe tip M2 KU1000/-R L20 D1.0/14.0

L = 20 mm; 1 mm ruby ballArt. IM05 1207

Probe tips M2 with diamond tip

For the exact determination of the surface parameters. Probe tip M2 KE5/90GD L5 D3 M2 L = 5 mm; diamond tip 90°/5 μ m Art. 1002 9793 Probe tip M2 KU1000/-R L15 D1.0/9.0 Probe tip M2 KE5/90GD L15 D3 M2

> L = 15 mm; diamond tip 90°/5 μ m Art. 1002 5091

Probe tips M2 with cone

For measurements on ground and lightly soiled measuring points. Probe tip M2 KE300/90H L5 D3/M2 L = 5 mm; cone tip 90°/0.3 mm Art. 1004 4157 Probe tip M2 KE300/90H L10 D3/M2 L = 10 mm; cone tip 90°/0.3 mm Art. 1004 4188 Probe tip M2 KE300/90H L15 D3/M2 L = 15 mm; cone tip 90°/0.3 mm Art. 1004 4189

Permanent measurement accuracy

DAkkS-DKD calibration laboratory

Continuous monitoring of optimum measurement accuracy is necessary to ensure perfect functioning of the measuring instruments. This is because changes in function can occur over the course of normal use, especially due to wear and tear, and these types of changes can go unnoticed. We calibrate the standards you send us in our ISO/IEC 17025 accredited DAkkS-DKD calibration laboratory. This ensures direct tracing of the gaging components to the Federal Physical-Technical Institute (PTB) and guarantees measurements and calibrations at the highest technical standard for measuring.

If a standard cannot be calibrated, a new one can be obtained directly from any of our manufacturing facilities. Simple factory calibration certificates and test reports for non-accredited parameters are also available. We also carry out capability tests for demanding measurement tasks.

Our range of calibration services

Our DAkkS-DKD accreditation includes the measurement of variables such as roughness, profile depth, roundness, straightness, and parallelism as well as contour standards and roughness measurement instruments. Within this scope we offer DAkkS-DKD calibration certificates:

- for form standards
- for cam shaft standards
- for contour standards
- for roughness standards

DAkkS-DKD calibration certificate for form standards

Calibration is carried out on our DAkkS-DKD measuring station in an air-conditioned, vibration-insulated measuring room. All common form characteristic values can be determined.





Magnification standard FN101

For inspecting the amplification of the pro	bing system.
With test report	Art. 521 809
With DAkkS-DKD calibration certificate	Art. 532 528



Roundness standard FN111

Made of ceramic. For inspecting the radial roundness deviation of the rotational axis.

With	test report			Art.	521	799
With	DAkkS-DKD	calibration	certificate	Art.	532	529



Roughness standard RNDX2 with standard holder FNR

Standard made of nickel with an extra hard protective coating and triangular/sinusoidal grooves. For inspecting the roughness measurement of the Z and R axis.

Delivered with test report and standard holder FNR for one or two geometry standards of the RNDH or RNDX type. Ra: approx. 1.0 µm; Rz: approx. 3.3 µm Art. 1003 4205



Set of twist standards

For inspecting the accuracy of the measuring systems. Calibrated parameters: Dt, DP, DG and D γ .

Delivered with test report. Art. 1001 6265



hommel etamic сғмзото

Comprehensive competence for crank shafts, gear shafts and cam shafts

Measure your crank shafts and cam shafts quickly and accurately with the fully automatic, CNC controlled CFM3010 measuring machine.

Highlights HOMMEL-ETAMIC CFM3010

- Secure measurement results, as there are no mechanical transverse forces
- Excellent basic accuracy thanks to high-resolution measurement systems
- Robust construction with vibration decoupling for use in the measuring room or in the laboratory
- Optimized CNC runs in conjunction with high measurement and travel speeds
- Can be used flexibly for a variety of workpieces

System features

- Gaging component capability: measuring accuracy with repeatability of up to 0.3 μm
- Distance between tips: 1250 or 1500 mm
- Fast measurement value recording
- Choice of manual or automatic loading
- Wear-free air bearing measuring slides
- Capable evaluation software TURBO SHAFT for cam shafts and crank shafts



HOMMEL-ETAMIC CFM3010

Model	Workpiece weight	Test diameter	Measuring height
CFM3010	150 kg	300 mm	1250 or 1500 mm

hommel etamic ccm

Specialist for cam shaft and cam form deviation measurements

Maximum mechanical accuracy and production-oriented robustness coupled with proven evaluation software are just some of the outstanding features of this CNC controlled cam shaft measuring machines.

Highlights HOMMEL-ETAMIC CCM2010/2020

- Horizontal structure for optimum handling of workpieces
- Measurement of all cam form deviations using suitable cam fitting processes
- Two measuring heads used in parallel ensure fast measurement runs
- Optimized CNC runs in conjunction with high measurement and travel speeds
- PTB certified evaluation algorithms

System features

- Continuous zero-point inspection of the measurement systems for optimum intrinsic machine safety
- Wear-free thanks to pneumatic tailstock lifting for positioning
- Robust construction and dual vibration decoupling for use in the metrology lab or in production
- High-resolution measurement systems for excellent basic accuracy



Model	Workpiece weight	Test diameter	Workpiece length	Measuring heads
CCM2010	50 kg	120 mm	1100 mm	1
CCM2020	50 kg	120 mm	1000 mm	2

Convenient measurement and evaluation according to standards



The Windows software TURBO SHAFT sets standards with its convenient operation and functionality:

- Fast and simple program creation thanks to standardized input assistance
- Extensive help functions
- Automatic creation of a CNC program with the input data
- Grouping functions support the clarity of complex CNC programs
- Entering of positions via teach-in
- "Copy & Paste" for recurring characteristics, tolerances and nominal values

Highlights HOMMEL-ETAMIC TURBO SHAFT

- Definition of all measurement positions by entering a constant bearing and measurement track distance
- All measured values can be displayed for direct evaluation during the CNC run
- Automatic evaluation and determination of characteristics
- Documentation of measurement results using clear screen and print forms
- Export in ASCII format
- Saves and exports source data, result data and reports
- Offline programming

Evaluation of specific measurement tasks



Chattermarks on cams



Axis parallelism



Cam form profile over 360°

The cam form profile deviation can be detected in the area of the pre-cams, main cams or post-cams as well as on the base circle.

Chattermarks

Chattermarks are detected thanks to a frictionless measurement system with no reverse tension. As the measured values are recorded in the regular cam form measurement, there is no additional time outlay.

Axis parallelism of crank shaft pin bearings

Display of the direction and amount of the axis parallelism to a reference axis for each main bearing and pin bearing via vectors.

Wear evaluation for cam shafts

Determination of the material wear between two measurements. The form deviation difference is identified as the maximum wear with the amount and angle position.

Crowning evaluation

Either from the polar or the linear measurement.

Certified qs-STAT® interface

ASCII transfer format for local or central data storage.



Crowning envelope line

Position deviation

Accessories for CFM and CCM

We offer a wide range of standard and custom accessories for easy handling of the workpiece. Our decades of experience in the field of crank shaft and cam shaft measurement ensure that you get the perfect solution even for complex measurement tasks.

Measuring followers

Universal measuring followers for different measuring tasks.



Flat measuring follower for crank shafts and convex cam shafts



Round measuring follower made of different materials for cam shaft diameters

Workpiece drivers

Universal standard workpiece drivers for the measurement of all common workpiece types. Application-specific drivers are also available.



Universal driver for cam shafts, gear shafts and crank shafts



Workpiece-specific axial driver for cam shafts and crank shafts for angle indexing in axial bores



Workpiece-specific radial driver for cam shafts for angle indexing in grooves

Cam form deviation measurements at PTB* level



Physikalisch-Technische Bundesanstalt

Prüfbericht

TURBO SHAFT Version 1.8.2.11 Interface 08.09.15

ced other than in full

Auswertesoftware für Nocken Evaluation software for cam

HOMMEL-ETAMIC GmbH Alte Tuttlinger Straße 20 78056 VS-Schwenningen

HOMMEL-ETAMIC GmbH Alte Tuttlinger Straße 20 78056 VS-Schwenningen

Braunschweig, 2011-12-20

5.3-2011-059 5.3-2011-059

2011-09-20

Siegel

weig und Berlin

Gegenstand

Hersteller:

6. Imil

Thanks to the cam shaft standard and the validated evaluation algorithms of the TURBO SHAFT software, traceable cam form deviation measurements can be performed for the first time.

- PTB certified evaluation software for cam shafts
- DAkkS-DKD calibrated cam shaft standard
- Practice-oriented, reliable, traceable and therefore comparable status reports and status evaluations of cam shaft measurement systems
- Evaluation of form and dimensional deviations in all the main characteristics
- Comparability of evaluation strategies and detached consideration of the influence of the software from a purely mechanical measurement process
- Evidence of gaging machine capability (Cg, Cgk)
- For all CFM and CCM measuring machines

Characteristics measured

- Cam form
- Cam pitch

ΡĪΒ

- Cam height
- Cam width
- Cam base circle radius
- Cam base circle run-out
- Cam angle position
- Diameter
- Circularity
- Straightness
- Parallelism
- Cylindricity

PTB-certified evaluation software TURBO SHAFT

- Validation of evaluation algorithms
- Definition of measuring uncertainty on the basis of synthetic reference information
- Certified measuring uncertainty of the software $_{\pm 0.1~\mu m}$ (cam form) or $\pm 0.1^{\prime\prime}$ (angle)

* Federal Physical-Technical Institute – Physikalisch-Technische Bundesanstalt (PTB)





Flexible measuring systems for form and roundness in cylinder bores

The incometer V measuring systems offer fast, reliable and highly accurate measurements for analytic examination of cylinder-piston configurations in engine block development.

Highlights HOMMEL-ETAMIC incometer V

- Flexible and mobile use during development and testing
- Resistant to vibrations, making it ideal for measurements during production
- Easily adapted to different cylinder dimensions thanks to the clamping mechanism
- The probe's self-adjustment eliminates time-consuming alignments
- Automatic correction of any eccentricities or inclined positions of the cylinder axes to the measuring probe via the software
- Shortest measuring times on the market

- Measurement of cylinder distortion and wear, also under temperature influences
- Assistance for the dimensioning of piston rings
- Measurement with mounted cylinder head possible
- Compact, robust measuring probe
- Scanning measuring method
- Simple operation via Windows software with pre-defined measuring routines
- By changing measuring tips and clamping jaws, the probe easily adjusts to different diameters





External plate for fixing the probe



HOMMEL-ETAMIC incometer VS

Measuring cylinder distortions

- Measurement and evaluation of the influence of cylinder heads and gaskets on bore distortion
- Thanks to its extremely compact design, the incometer probe can be installed on the crank shaft side in order to measure inside cylinder bores with the cylinder head mounted
- In the case of long-term testing, wear rates and cylinder distortion can also be monitored

Temperature distortion

- Simple fixturing and high speed allow for measurement of engine blocks, even under high temperature conditions
- Distortion-specific analysis of the critical warm-up phase with extreme differences in temperature between the cylinder head and the engine block

incometer VS for small engines

Analysis of cylinder distortions in small motors, e.g. for:

- Motorcycles
- Agricultural and forestry equipment
- Compressors of cooling systems

incometer V110 for flat engines

Analytical testing of the cylinder-piston configuration in engines with particularly difficult installation requirements, e.g. extremely flat V engines.



HOMMEL-ETAMIC incometer V110



Mounting device and accessories for HOMMEL-ETAMIC incometer V

Model	Test diameter	Axial measuring range	Radial measuring range
incometer V	65 – 155 mm	80–200 mm (depending on model)	±400 μm
incometer V110	65 – 155 mm	110 mm	±400 µm
incometer VS120	39 – 100 mm	120 mm	±500 μm





HOMMEL-ETAMIC incometer P

Fast form measurement in cylinder bores

The incometer P delivers fast, reliable and highly accurate quality data during production.

Highlights HOMMEL-ETAMIC incometer P

- Fast measurement readiness, as no manual alignment is required
- Measurement of the cylinder bore in just a few seconds
- Fast adaptation to different bore diameters thanks to interchangeable measuring tips
- Ideally suited for flexible production lines
- Simple operation, even without previous experience

- Compact and robust design for mobile use during production
- Minimization of disruptive vibrations thanks to direct mechanical connection between the measuring probe and the workpiece
- Automatic correction of inclinations and eccentricities by the software
- Precision measurements of roundness and form in seconds during engine production



Inserting of the probe



Fixing of the probe

Easy handling and fast measurement

Measuring a cylinder bore with the incometer P takes only a few seconds:

homme

incometer P

- Insertion of the probe into the cylinder
- Plastic guide rails protect the cylinder wall
- Adjustment of the probe to the bore via a fixture plate
- Simply attaching the clamping levers connects the incometer P to the engine block
- Start of the measurement and 360° rotation of the measuring head
- Scanning, dynamic recording of the measurement values of all previously positioned sensors at a constant speed
- Measurement values are available immediately
- Choice of up to 7 sensors per measuring head



Isometric plot of a cylinder measurement



Radial plot of a cylinder bore



Axial plot of a cylinder bore

Model	Test diameter	Axial measuring range	Radial measuring range
incometer P100	60 – 110 mm	max. 300 mm	\pm 500/1000 μ m (depending on the diameter)





Clearly structured evaluation and control software



Clearly arranged desktop

The clearly structured INCOWIN software ensures that operating the measuring systems is easy, even with no previous experience. Once the measurements have been taken, all procedures, such as saving and printing the measurement results and statistically evaluating them, can be performed automatically. The advanced user administration (optional) allows hierarchical access to the individual functions of the INCOWIN software.

Highlights HOMMEL-ETAMIC INCOWIN

- Optimal mobility with a notebook
- Clear and easy-to-understand user interface for intuitive operation
- Central data backup possible via network operation
- Rapid set-up of all user-specific requirements
- Multiple display options for easy analysis of the measurement results
- Easy creation of new measurement reports
- Customization of screen and print forms
- Language selection (English, German, French) during operation
- Simple project management
- Comfortable menu guidance



Dynamic measurement

INCOWIN offers extensive measuring functions and is equipped with a standardized high-resolution scanner. This ensures a very high resolution and a detailed display of the actual geometry of the cylinder bore. The high data density allows standardized filter methods to be used (e.g. Fourier and Gauss filters or median filter for eliminating individual outliers).

Optimum mobility

The incometer systems are operated with a notebook for mobile use. The overall logic is generated on an interface card, which is installed in the electronics unit. The connection to the computer consists of a serial interface cable.

Unrestricted upgrade capability

Measurement systems can be retrofitted at any time. The cost will vary depending on the age and technological status of the system, and must be determined on a case-by-case basis.

Customizable range of functions

INCOWIN can be extended by software options and the range of functions can be customized, thereby ensuring maximum clarity.

Optional offline software

This module enables external (offline) evaluation and analysis of the measurement data from the incometer form measuring system on a separate computer.

Software options for research and development



Wear measurement



Fourier analysis



Wear measurement

In order to measure the liner wear in previously used cylinder bores, the cylinder bore is measured in high resolution with axial scans equally distributed around the circumference.

Measuring temperature distortion

Due to the very fast complete cylinder measurement, the incometer systems are also able to measure hot engines (up to over 120°C), allowing temperature distortion to be identified on a "living" object.

Fourier analysis

Distortions are calculated using the Fourier analysis method for a more precise description of the cylinder form.

"Copy & Paste"/Data export

Both the graphics and the parameter list can be exported to another format or to other Windows applications.

Differentiation

For analyzing distortion changes with different configurations of the cylinder head, the cylinder head seal and the crankcase, or for hot distortion evaluations. A difference is generated based on measurements that have been carried out at different times in order to draw a direct comparison between them.

Data import

External data (polar, Cartesian or as Fourier coefficients) can be imported into the INCOWIN software, evaluated with the same algorithms as "normal" measurements, and compared with the incometer measurements.

Differentiation

Software options for the production



Block measurement



gs-STAT[®] interface



Block measurement and complete evaluation

For measuring a complete crankcase with one-time input of the reference data. The user is guided through the entire measuring procedure via diagrams. All cylinder measurements of a crankcase are saved in a single file. The evaluation contains the printout of the form parameters for all cylinders in a table and provides a graphic display of the radial and axial measurement and the isometries for all cylinders on one page.

Data transfer to qs-STAT®

The qs-STAT[®] interface certified by Q-DAS allows the measurement results to be transferred to a statistics package for further process data analysis.

Determining the absolute diameter

For determining the absolute diameter of the cylinder of a crankcase. To this end, the incometer is calibrated to the nominal dimension of the cylinder diameter before each measurement.

Advanced user administration

For creating different users and user groups with their own profiles. The individual users can each be assigned to a specific group and given a personal password.

Automatic functions

For automating processes, such as saving, printing etc., in order to reduce errors resulting from incorrect inputs or user mistakes.

User administration

Technical data

HOMMEL-ETAMIC F series and roundscan systems

Model	F50	F135 / F155	F435 / F455	roundscan 535 / 555 / 590
Measuring range Distance C/Z axis, max. interfering edge radius Max. test diameter Max. measuring height	195 mm 300 mm 320 (560) mm	275 mm 340 mm 350 / 550 mm	325 mm 430 mm 350 / 550 mm	370 (420*) mm 430 (530*) mm 350 / 550 / 900 mm
Rotation axis (C axis) Table diameter Workpiece alignment Roundness error µm+µm/mm measuring height Roundness error µm+µm/mm radius Axial run-out error µm+µm/mm radius** Centering range Leveling range Measuring and positioning speed Bearing Max charge	150 mm manual 0.05+0.0005 μm 0.025+0.00025 μm 0.05+0.0005 μm 0.025+0.00025 μm ±2 mm ±0.6° 1–10 1/min. air 250 N	150 mm manual 0.03+0.0005 μm 0.015+0.00025 μm 0.02+0.00025 μm ±2 mm ±0.6° 1-10 1/min. air 250 N	250 mm automatic 0.02+0.0005 μm 0.01+0.00025 μm 0.03+0.0005 μm 0.015+0.00025 μm ±2 mm ±0,6° 1-12 1/min. air 400 N	330 mm automatic 0.02+0.0005 μm 0.01+0.00025 μm 0.03+0.0005 μm 0.015+0.00025 μm ±5 mm ±1° 0,2-30 1/min. air 600 (1000)* N
Vertical axis (Z axis) Traverse distance Measuring distance Straightness error/100 mm Straightness error/measuring distance Parallel C-Z/measuring distance Measuring and positioning speed Collision protection	320 mm 	- 350 / 550 mm 0.15 μm 0.3 / 0.4 μm 0.8 / 1.3 μm 0.2–23 mm/s yes	- 350 / 550 mm 0.15 μm 0.3 / 0.4 μm 0.8 / 1.3 μm 0.2–23 mm/s yes	- 350 / 550 / 900 mm 0.15 / 0.15 / 0.25 µm 0.3 / 0.45 / 1.5 µm 0.5 / 0.8 / 2.5 µm 0.2–50 mm/s yes
Horizontal axis (R axis) Traverse distance Measuring distance Straightness error/100 mm Straightness error/measuring distance Squareness C-R Measuring and positioning speed	160 mm - - - -	_ 220 mm _ _ _ 0.2–14 mm/s	– 220 mm 0.3 µm 0.6 µm 1.2 µm 0.2–14 mm/s	– 220 mm 0.25 μm 0.5 μm 0.8 μm 0.2–50 mm/s
Dimensions/weight Length Width Height Weight (approx.)	475 (635) mm 285 mm 710 mm 60 kg	700 (910)*** mm 410 (550)**** mm 950 / 1150 mm 185 / 200 kg	790 (1010)*** mm 510 (650)*** mm 960 / 1160 mm 290 / 300 kg	1990 mm 750 mm 1760 / 1960 / 2310 mm 650 / 665 / 685 kg

All accuracy data according to EN ISO 1101 at 20°C \pm 1°C in vibration neutral environment. Filter 0–15 rpm LSCI, or 2.5 mm LSLI; 6 rpm, or 4 mm/s. All proof on standard under inclusion of the compensation method.

* On request ** Values as maximum deviation from the reference circle LSCI, filter 0-15 rpm LSC, 6 rpm *** R axis extended **** With servo box

HOMMEL-ETAMIC FMS8200

Model FMS8200 Measuring range Max. test diameter 300 mm Max. measuring height 1250 (1500)* mm Max. traverse distance radial 210 mm Rotation axis (C axis) Dimensions table 600 x 450 mm automatic Workpiece alignment 0.1+0.0008 µm Roundness error radial µm+µm/mm measuring height Axial run-out error µm+µm/mm 0.1+0.0008 µm radius Bearing air Max. charge 3000 N Traversing speed max. 12 rpm Resolution 0.01° Positioning accuracy 0.1° Vertical axis (Z axis) Measuring distance 1300 mm Straightness error/100 mm 0.3 µm Straightness error/measuring distance 2,6 µm Measuring speed 16 mm/s Positioning speed 25 mm/s Positioning error/measuring distance 15 µm/1300 mm Horizontal axis (R axis) Measuring distance 150 mm + 100 mm rel. Straighntness error/150 mm 1.5 µm Measuring speed 16 mm/s Positioning speed 25 mm/s Positioning error/measuring distance 5 µm/150 mm Straightness axis (X axis) measuring Measuring distance 800 mm Straightness error/100 mm 0.3 µm Straightness error/measuring distance . 1.6/800 mm Measuring speed 16 mm/s Positioning speed 25 mm/s Positioning error/measuring distance 10 µm/800 mm Straightness axis (Y axis) measuring Measuring distance 300 mm Straightness error/100 mm 0.3 µm Straightness error/measuring distance 0.9 µm/300 mm Measuring speed 16 mm/s Positioning speed Positioning error/measuring distance 25 mm/s 6 µm/300 mm Dimensions/weight Length 1704 mm Width 2250 mm Height 3316 mm Weight (approx.) 7500 kg

HOMMEL-ETAMIC CFM3010 and CCM2010/CCM2020

Model CFM3010		CCM2010 / CCM2020
Measuring range Distance C/Z axis, max. interfering edge radius* Max. test diameter Max. measuring height Max. traverse distance radial	162 mm 300 mm 1250 (1500) mm 210 mm	175 mm 118 mm 1100 / 1000 mm 60 mm
Rotation axis (C axis) Face plate Workpiece alignment Measuring speed Bearing Max. charge Traversing speed Resolution Positioning accuracy Accuracy Run-out accuracy of the roller bearing	196 mm tips 2–40 1/min. mechanical 1500 N 2–40 1/min. 0.00005° 0.1° ±0.00028 0.25 µm	157 mm tips 2–40 1/min. mechanical 500 N 2–40 1/min. 0.0001° 0.1° 0.00139° < 0.5 μm
Vertical axis (Z axis) Travel distance Measuring distance Collision protection Positioning speed Positioning error/measuring distance Measuring and positioning speed Resolution of the Z scale Accuracy	1290 (1590)** mm 1250 (1500)** mm yes 5–150 mm/s 0.05 mm 5–150 mm/s 0.1 μm ±3 μm	1200 / 1000 mm 1170 / 935 ¹⁰ mm optional 5–200 mm/s 0.1 mm 200 mm/s 0.1 μm ±3 μm
Straigtness axis (X axis) Measuring distance Resolution Accuracy Setting range of measurement force	210 mm 0.02 μm ±0.2 μm 1, 2, 3 and 4 N	60 mm 0.1 μm ±0.5 μm 1, 2, 3 and 4 N
Travel in X direction Measuring point distance Resolution radial Resolution axial	0.1/0.2/0.5/1 0.02 μm 0.1 μm	0.1/0.2/0.5/1 0.1 μm 0.1 μm
Dimensions/weight Length Width Height Weight (approx.)	1240 mm 1360 mm 2450 mm 2400 kg	2000 mm 1000 mm 1150 mm 1500 kg

* Standard flat measuring follower, length 43 mm

** On request

¹⁾ CCM2020: 935 per measuring slide

Technical data

HOMMEL-ETAMIC incometer systems

Model	incometer	V			incometer VS	incometer P	
	V80	V115	V150	V200	V110	VS120	P100
Diameter of the cylinder*		^	65 – 155 mm	ו	39 – 100 mm	60 – 110 mm	
Clamping length min.	20 mm	20 mm	25 mm	30 mm	40 mm	ext. fixture	ext. fixture
Axial measuring range	80 mm	115 mm	150 mm	200 mm	110 mm	120 mm	max. 300 mm
Measuring path on the circumference		^	360°		360°	360°	
Radial measuring range			± 400 µm		± 500 μm	± 500/1000 µm***	
Resolution			0.1 µm		0.1 µm	0.1 µm	
Number of measured values per rotation			14,400/1,024	4	14,400/1,024	14,400/1,024	
Number of sensors			1		1	max. 7	
Repeating accuracy Roundness Cylinder form Parallelism			≤ 1.0 µm ≤ 1.5 µm ≤ 1.5 µm		≤ 1.0 μm ≤ 1.5 μm ≤ 1.5 μm	≤ 1.0 µm ≤ 1.0 µm -	
Measuring accuracy Roundness Cylinder form Parallelism			≤ 1.0 µm ≤ 1.5 µm ≤ 1.5 µm		≤ 2.0 μm ≤ 2.0 μm ≤ 2.0 μm	≤ 1.0 μm ≤ 1.5 μm −	
Temperature range of use**			20 – 40 °C		20 – 40 °C	20 – 40 °C	
Power supply			230 V/50 Hz 115 V/60 Hz		230 V/50 Hz 115 V/60 Hz	230 V/50 Hz 115 V/60 Hz	
Power consumption			150 W		150 W	150 W	
Weight of the sensor	2.9 kg					1.9 kg	8 kg***

* Further diameters on demand ** Measuring of the warm distortion on demand (up to 130°C) *** Dependent on diameter

Product range for incometer	ø min/max	Height / Depth	Width of part	Laboratory	Offline
Cylinder bore	39 – 155 mm	≤ 200 mm	≤ 200 mm	incometer VS incometer V	incometer P
Cylinder liners	39 – 155 mm	≤ 200 mm	≤ 200 mm	incometer VS incometer V	incometer P

Excellent industrial metrology

WAVELINE Roughness and Contour Metrology

Mobile, manual and automated measuring instruments for determining roughness, contour, topography and twist; combined systems for roughness and contour measurements; optical surface inspection for cylinder bores and customized solutions.

FORMLINE

Manual and CNC-controlled systems for measuring form, position and twist, combined form and roughness instrumentation, form measurement systems for cylinder bores, spindle measuring machines, crank shaft and cam shaft measuring machines and workpiece-specific solutions.

OPTICLINE Optical Shaft Metrology

Optical measuring systems for determining dimensions, form, position and geometric elements on concentric workpieces. Can be used offline, or as an automated SPC measuring station within the production chain and as a customized solution for workpiece-specific requirements.

GAGELINE -Dimensional Metrology

Pre-process, in-process and post-process measuring systems for measuring dimensions via tactile, pneumatic or optical technologies, including manual, semi and fully automatic systems, final inspection machines and individual in-line systems, plus systems for optical surface inspection.

MOVOLINE

Digital measuring heads, control devices and accessories for tactile in-process measurements of diameter, position and length in machine tools, all aimed at controlling the machining process of machine tools.



Metrological services including training, application studies and start-up support, relocation services, production monitoring, (remote) services and calibration, repairs and spare parts/replacement service, measuring program generation and measurement process optimization.





Head Office JENOPTIK Industrial Metrology Germany GmbH Alte Tuttlinger Straße 20 78056 VS-Schwenningen Germany

Close to you. Group companies in

- Germany France Switzerland Spain Czech Republic
- ico il
- China Singapore South Korea India

Affiliates and representation worldwide: www.jenoptik.com/metrology

Please contact us: info.im@jenoptik.com